

N-type waterproof female head extension wire 250mm

behaviour of electricity	
model	XHDYCXNKIPEX1178250
Frequency Range (MHz)	0-3000/3000-6000
impedance (Ω)	50
Insulation impedance (m Ω)	≥ 5000
Insulation withstand voltage (AC) (KV)	2.0
Sheacket spark voltage (KV)	5.0
peak power (KW)	9.23
screening effectiveness (dB)	> 90
voltage standing-wave ratio	$\leq 1.2 / \leq 1.3$
insertion loss (dB)	$\leq 0.15 / \leq 0.15$
Internal conductor jack material / coating	Brass Gold / Brass Gold
Insulation material	teflon
Material / coating of shell and outer conductor	Brass Gold / Brass Gold
Seal material	silastic
power capacity (W)	300
mechanical behavior	
joint categories	The N-K/IPEX 1 generation
Cable material	Copper dip tin
Cable model	RG178
product size (M)	250
working temperature ($^{\circ}\text{C}$)	$-55 \sim 125$
ultimate temperature ($^{\circ}\text{C}$)	$-65 \sim 175$
Minimum bending radius (mm)	7.5
Minimum bending temperature of ($^{\circ}\text{C}$)	-15
pack	1PCS / bag
classification of waterproof	IP65
	